



CILINDRI COMPACTI tip PEC

CU DISPOZITIV ANTI-ROTATIE
DUBLA ACTIUNE Ø 20 la 100 mm
compatibili cu ISO 21287

pregatiti pentru detectori magnetici de pozitie

CARACTERISTICI

Fluide	aer gaz neutru, filtrat, lubrificat sau nu
Presiunea de lucru	max. 10 bar
Temperatura	-20°C la +70°C
Viteza maxima admisa	0,5m/s
Corp	aliaj de aluminiu
Tija	Ø20: inox , Ø25-100: otel cromat
Etansari	NBR (nitrile)
Amortizare	elastica
Standard	compatibili cu accesoriile de montaj standardizate Ø20-25: ISO 21287 Ø32-100: ISO 15552-AFNOR NF ISO 15552-DIN ISO 15552
Racorduri	M5 (Ø 20 - 25 mm) G1/8 (Ø 32 - 100 mm) G1/4 (Ø 100mm)

- Doua tije de ghidare/blocare rotatie
- Control perfect al pozitiei unghiulare a sarcinii
- Lagarele auto-lubrificate, permit reducerea frecarii si asigura o excelenta fiabilitate
- Suporta sarcini mari

ALEGEREA PRODUSULUI

Ø mm	cursa mm	referinta	cod	Ø mm	cursa mm	referinta	cod
dubla actiune Ø 20 la 100 mm							
20	10	PEC 20 NA 10 L-DM	44956C020010	50	15	PEC 50 NA 15 L-DM	44956C050015
	20	PEC 20 NA 20 L-DM	44956C020020		20	PEC 50 NA 20 L-DM	44956C050020
25	10	PEC 25 NA 10 L-DM	44956C090010		25	PEC 50 NA 25 L-DM	44956C050025
	20	PEC 25 NA 20 L-DM	44956C090020		30	PEC 50 NA 30 L-DM	44956C050030
32	15	PEC 32 NA 15 L-DM	44956C030015		50	PEC 50 NA 50 L-DM	44956C050050
	20	PEC 32 NA 20 L-DM	44956C030020	80	PEC 50 NA 50 L-DM	44956C050080	
	25	PEC 32 NA 25 L-DM	44956C030025	63	15	PEC 63 NA 15 L-DM	44956C060015
40	PEC 32 NA 40 L-DM	44956C030040	20		PEC 63 NA 20 L-DM	44956C060020	
50	PEC 32 NA 50 L-DM	44956C030050	25		PEC 63 NA 25 L-DM	44956C060025	
40	15	PEC 40 NA 15 L-DM	44956C040015		30	PEC 63 NA 30 L-DM	44956C060030
	20	PEC 40 NA 20 L-DM	44956C040020		50	PEC 63 NA 50 L-DM	44956C060050
	25	PEC 40 NA 25 L-DM	44956C040025	80	PEC 63 NA 80 L-DM	44956C060080	
40	30	PEC 40 NA 30 L-DM	44956C040030	80	50	PEC 80 NA 50 L-DM	44956C080050
	40	PEC 40 NA 40 L-DM	44956C040040		80	PEC 80 NA 80 L-DM	44956C080080
	50	PEC 40 NA 50 L-DM	44956C040050	100	50	PEC 100 NA 50 L-DM	44956C010050
	80	PEC 40 NA 80 L-DM	44956C040080		80	PEC 100 NA 80 L-DM	44956C010080
				100	PEC 100 NA 100 L-DM	44956C010100	

DIMENSIUNI

(vezi paginile urmatoare)

OPTIUNI SI ACCESORII

Dispozitive de montaj
(vezi pag. 41)



Detectori de pozitie
(vezi pag. 50)



Drozele
(vezi pag. 108)



Alte curse si diametre
la cerere